

LENOCEAN

HZS25E/F 混凝土搅拌楼 HZS25E/F CONCRETE BATCHING PLANT

HZS25E/25F

- Equipped with twin shaft forced mixer
- Compact design, Economical, and Easy-to-maintain
- Skip Aggregate Hoist
- Custom designed (Manual or Computerized Control System)
- Mix design memory, difference compensation
- Easy to transport and install
- Optional cement silo or cement feeder

LENOCEAN

BEIJING LENOCEAN TALENT INT. INDUSTRY CORPORATION
www.lenoccean.com

HZS25E/F混凝土搅拌站性能参数

HZS25E/F CONCRETE BATCHING PLANT PARAMETERS

BEIJING LENOCEAN TALENT INT. INDUSTRY CORPORATION

www.lenoccean.com

● HZS25E

	项目Item	单位Unit	技术参数 Technical parameters
	JS500 搅拌机 (Mixer)	出料容积(Discharge Capacity)	升(L)
进料容积(Charge Capacity)		升(L)	800
搅拌时间(Mixing Time)		秒s	35-45
额定生产率(Rated Output)		立方/小时	25
主电机功率(Motor Power)		千瓦(kw)	18.5
提升电机功率(Hoisting power)		千瓦(kw)	5.5
水泵电机功率(Pump power)		千瓦(kw)	2.2
骨料最大粒径(碎石/卵石) (Max diameter of aggregates gravel/ crushed stone)		毫米(mm)	60/80
外型尺寸(Overall Dimension)		毫米(mm)	10143×2612×7426
整机质量(Total Weight)		kg	4000
PL800 四斗配料机 Four Batching	储料斗容积(Storage Bucket Capacity)	m ³	4*4
	计量斗容积(Weigher Capacity)	L	800
	电机功率(Motor Power)	kw	4
	振动电机(Vibrating Motor)	kw	0.3
	外型尺寸(Overall Dimension)	mm	11130×2100×2800
整机质量(Total Weight)	kg	4000	
螺旋输送机 Screw Conveyor	型号(Type)		LSJ20
	输送长度(Conveyor Length)	mm	11250
	螺旋体转速(Screw Turning Speed)	r/min	225
	外壳体直径(Diameter)	mm	φ219
	工作角度(Working Angle)	40°	
	输送能力(Conveying Ability)	t/h	20
	电机型号(Motor Type)	Y132M-4/B5	
	电机功率(Motor power)	kw	7.5
外型尺寸(Overall Dimension)	mm	11250×1202×350	
整机质量(Total Weight)	kg		
水泥散装斗 Cement Feeder	外型尺寸(Overall Dimension)	m	1.96×1.96×2
水泥计量斗 Cement Weigher	容积(Capacity)	L	
	外型尺寸(Overall Dimension)	mm	1660×870×1080
	整机质量(Total weight)	kg	
空压机 Compressor	型号 Type	0.17/8	
	排气量 Discharging Volume	m ³ /minute	0.17
	额定压力 Rated Pressure	mpa	0.8
	电机功率(Motor Power)	kw	3

Users may install Cement Silo at own option.

● HZS25F

	项目Item	单位Unit	技术参数 Technical parameters
	JS500 搅拌机 (Mixer)	出料容积(Discharge Capacity)	升(L)
进料容积(Charge Capacity)		升(L)	800
搅拌时间(Mixing Time)		秒s	35-45
额定生产率(Rated Output)		立方/小时	25
主电机功率(Motor Power)		千瓦(kw)	18.5
提升电机功率(Hoisting power)		千瓦(kw)	5.5
水泵电机功率(Pump power)		千瓦(kw)	2.2
骨料最大粒径(碎石/卵石) (Max diameter of aggregates gravel/ crushed stone)		毫米(mm)	60/80
外型尺寸(Overall Dimension)		毫米(mm)	10143×2612×7426
整机质量(Total Weight)		kg	4000
PL800 四斗配料机 Four Batching	储料斗容积(Storage Bucket Capacity)	m ³	4*4
	计量斗容积(Weigher Capacity)	L	800
	电机功率(Motor Power)	kw	4
	振动电机(Vibrating Motor)	kw	0.3
	外型尺寸(Overall Dimension)	mm	11130×2100×2800
整机质量(Total Weight)	kg	4000	
螺旋输送机 Screw Conveyor	型号(Type)		LSJ20
	输送长度(Conveyor Length)	mm	11250
	螺旋体转速(Screw Turning Speed)	r/min	225
	外壳体直径(Diameter)	mm	φ219
	工作角度(Working Angle)	40°	
	输送能力(Conveying Ability)	t/h	20
	电机型号(Motor Type)	Y132M-4/B5	
	电机功率(Motor power)	kw	7.5
外型尺寸(Overall Dimension)	mm	11250×Φ350	
整机质量(Total Weight)	kg		
水泥破包斗 Cement Feeder	外型尺寸(Overall Dimension)	m	1.96×1.96×2
水泥计量斗 Cement Weigher	容积(Capacity)	L	500
	外型尺寸(Overall Dimension)	mm	1350×870×1080
空压机 compressor	型号 Type	0.17/8	
	排气量 Discharging Volume	m ³ /minute	0.17
	额定压力 Rated Pressure	mpa	0.8
	电机功率(Motor Power)	kw	3

Users may install Cement Silo at own option.

LENOCEAN

HZS50E/F 混凝土搅拌站 HZS50E/F CONCRETE BATCHING PLANT

HZS50E/50F

- Equipped with twin shaft forced mixer
- High-precision, large output, robust and reliable
- Skip Aggregate Hoist
- Custom designed (Manual or Computerized Control System)
- Mix design memory, difference compensation
- Easy to transport and install
- Optional cement silo or cement feeder



LENOCEAN

BEIJING LENOCEAN TALENT INT. INDUSTRY CORPORATION
www.lenoccean.com

HZS50E/F混凝土搅拌站性能参数

HZS50E/F CONCRETE BATCHING PLANT PARAMETERS

● HZS50E

	项目 Item		单位 Unit		技术参数 Technical parameters		
	JS1000B 搅拌机 (Mixer)	出料容积(Discharge Capacity)		升(L)		1000	
进料容积(charge Capacity)		升(L)		1600			
搅拌时间(Mixing Time)		秒(s)		35-45			
额定生产率(Rated Output)		m³/h		≥50			
主电机功率(Motor Power)		千瓦(kw)		18.5 × 2			
提升电机功率(Hoisting Power)		千瓦(kw)		18.5			
潜水泵电机功率(Submersible Pump Power)		千瓦(kw)		2.2			
骨料最大粒径(碎石/卵石) (Max diameter of aggregates gravel/crushed stone)		毫米(mm)		60/80			
外型尺寸(Overall Dimension)		mm		9500 × 3800 × 8605			
整机质量(Total Weight)		kg		11000			
PL1600 四斗配料机 Four Batching		储料斗容积(Storage Bin Capacity)		m³		4 × 4m³	
		计量斗容积(Weigher Capacity)		L		1600	
		电机功率(Motor Power)		kw		5.5	
	振动电机(Vibrating Motor)		kw		0.30		
	外型尺寸(Overall Dimension)		mm		12300 × 2200 × 2700		
整机质量(Total Weight)		kg		6500			
螺旋输送机 Screw Conveyor	型号(Type)		LSJ40		LSJ40 (for Cement Silo)		
	输送长度(Conveyor Length)		mm		11000 9000		
	螺旋体转速(Screw Turning Speed)		r/min		238.6 238.6		
	外壳体直径(Diameter)		φ 273		φ 273		
	工作角度(Working Angle)		40		35		
	输送能力(Conveying Ability)		t/h		40 40		
	电机型号(Motor Type)		Y160L-4B5				
	电机功率(Motor power)		kw		15 15		
	外型尺寸(Overall dimension)		mm		φ 450x12500 φ 450x10800		
整机质量(Total weight)		kg		15500			
水泥散装斗 Cement Feeder	外型尺寸(Overall Dimension)		m		1.96 × 1.96 × 2		
水泥计量斗 Cement Weigher	容积(Capacity)		L		650		
	外型尺寸(overall dimension)		mm		1660 × 870 × 1080		
	整机质量(Total weight)		kg		265		
空压机 Compressor	型号 Model		W-0.9/7		排气量 Discharging Volume 0.9M³/minute		
	额定压力 Rated Pressure		0.8mpa		电机功率 Motor Power 5.5kw		

● HZS50F

	项目 Item		单位 Unit		技术参数 Technical Parameters		
	JS1000B 搅拌机 (Mixer)	出料容积(Discharge Capacity)		升(L)		1000	
进料容积(Charge Capacity)		升(L)		1600			
搅拌时间(Mixing Time)		秒(s)		35-45			
额定生产率(Rated Output)		M³/h		≥50			
主电机功率(Motor Power)		千瓦(kw)		18.5 × 2			
提升电机功率(Hoisting Power)		千瓦(kw)		18.5			
潜水泵电机功率(Submersible Pump Power)		千瓦(kw)		2.2			
骨料最大粒径(碎石/卵石) (Max diameter of aggregates gravel/crushed stone)		毫米(mm)		60/80 60/80			
外型尺寸(Overall Dimension)		mm		9500 × 3800 × 8605			
整机质量(Total Weight)		kg		11000			
PL1600 四斗配料机 Four Batching		储料斗容积(Storage Bin Capacity)		m³		4 × 4m³	
		计量斗容积(Weigher Capacity)		L		1600	
		电机功率(Motor Power)		kw		7.5	
	振动电机(Vibrating Motor)		kw		0.30		
螺旋输送机 Screw Conveyor	外型尺寸(Overall Dimension)		mm		12300 × 2200 × 2700		
	整机质量(Total Weight)		kg		6500		
	型号(Type)				LSJ40 LSJ40 (for Cement Silo)		
	输送长度(Conveyor Length)		mm		11000 9000		
	螺旋体转速(Screw Rotating Speed)		r/min		238.6 238.6		
	外壳体直径(Diameter)		φ 273		φ 273		
	工作角度(Working Angle)		40		35		
	输送能力(Conveying Ability)		t/h		40 40		
	电机型号(Motor Type)		Y160L-4B5				
	电机功率(Motor Power)		kw		15 15		
水泥散装斗 Cement Feeder	外型尺寸(Overall Dimension)		m		1.96 × 1.96 × 2		
	水泥计量斗 Cement Weigher	容积(Capacity)		L		650	
		外型尺寸(Overall Dimension)		mm		1660 × 870 × 1080	
整机质量(Total Weight)		kg		265			
计量系统 Metering System	水计量斗 Water Weigher	容积(Capacity)		L		250	
		外型尺寸(Overall Dimension)		mm		1100 × 600 × 900	
		整机质量(Total Weight)		kg		171	
外加剂计量斗 Additive Weigher	容积(Capacity)		L		20		
	外型尺寸(Overall Dimension)		mm		φ 350 × 400		
整机质量(Total Weight)		kg		37			
空压机 Compressor	型号 Model		W-0.9/7				
	排气量 Discharging Volume		M³/minute		0.9		
	额定压力 Rated Pressure		mpa		0.8		
	电机功率 Motor Power		kw		5.5		

LENOCEAN

HLS75F 混凝土搅拌站 HZS75F CONCRETE BATCHING PLANT

HLS75F

- High efficiency, precise weighing system
- Wear-resistance, low maintain cost
- Belt Aggregate Conveyor, large concrete output
- PLC integrated, PC controlled
- Optional Cement Silo and Screw Conveyor



LENOCEAN

BEIJING LENOCEAN TALENT INT. INDUSTRY CORPORATION
www.lenoccean.com

HZS75F混凝土搅拌站性能参数

HZS75F CONCRETE BATCHING PLANT PARAMETERS

BEIJING LENOCEAN TALENT INT. INDUSTRY CORPORATION

www.lenoccean.com

●HZS75F

	项目Item	单位Unit	技术参数Technical parameters
JS1500 搅拌机 (Mixer)	出料容积(Discharge Capacity)	升 (L)	1500
	进料容积(Charge Capacity)	升 (L)	2400
	搅拌时间(Mixing Time)	秒s	35-45
	额定生产率(Rated Output)	立方/小时	75
	主电机功率(Motor Power)	千瓦(kw)	30x2
	提升电机功率(Hoisting power)	千瓦(kw)	22
	水泵电机功率(Pump power)	千瓦(kw)	3
	骨料最大粒径 (碎石/卵石) (Max diameter of aggregates gravel/crushed stone)	毫米(mm)	60/80
	外型尺寸(Overall Dimension)	毫米(mm)	10000x3800×11000
	整机质量(Total Weight)	kg	11700
PL2400 三斗配料机 Four Batching	储料斗容积(Storage Bucket Capacity)	m ³	3×6
	计量斗容积(Weigher Capacity)	L	2400
	电机功率(Motor Power)	kw	7.5
	振动电机(Vibrating Motor)	kw	0.3
	外型尺寸(Overall Dimension)	mm	9700x2750x3500
	整机质量(Total Weight)	kg	5800
螺旋输送机 Screw Conveyor	型号(Type)		LSJ65
	输送长度(Conveyor Length)	mm	9000
	螺旋体转速(Screw Turning Speed)	r/min	140
	外壳体直径(Diameter)	mm	273
	工作角度(Working Angle)		30-40°
	输送能力(Conveying Ability)	t/h	65
	电机功率(Motor power)	kw	15
	外型尺寸(Overall Dimension)	mm	9000XΦ350
100t水泥仓 Cement Feeder	外型尺寸(Overall Dimension)	m	20XΦ2.8
	容积(Capacity)	L	800
水泥计量斗 Cement Weigher	外型尺寸(Overall Dimension)	mm	1150x700x1950
	容积(Capacity)	L	300
水计量斗 Water Weigher	外型尺寸(Overall Dimension)	mm	1340x800x1000
	容积(Capacity)	L	40
外加剂计量斗 Additive Weigher	外型尺寸(Overall Dimension)	mm	Φ400x400
	容积(Capacity)	L	40
空压机 compressor	型号 Type		
	排气量 Discharging Volume	m ³ /minute	1.6
	额定压力 Rated Pressure	mpa	1
	电机功率(Motor Power)	kw	11

Users may install Cement Silo at own option.

LENOCEAN

HLS80 混凝土搅拌楼 HLS80 CONCRETE BATCHING PLANT

HLS80

- High efficiency, precise weighing system
- Wear-resistance, low maintain cost
- Belt Aggregate Conveyor, large concrete output
- PLC integrated, PC controlled
- Optional Cement Silo and Screw Conveyor

LENOCEAN

BEIJING LENOCEAN TALENT INT. INDUSTRY CORPORATION
www.lenoccean.com

HLS80混凝土搅拌楼性能参数

HLS80 CONCRETE BATCHING PLANT PARAMETERS

BEIJING LENOCEAN TALENT INT. INDUSTRY CORPORATION

www.lenoccean.com

● HLS80

	项目Item	单位Unit	技术参数 Technical parameters
JS1500 搅拌机 (Mixer)	出料容积(Discharge Capacity)	升 (L)	1500
	进料容积(Charge Capacity)	升 (L)	2400
	搅拌时间(Mixing Time)	秒s	30-45
	额定生产率(Rated Output)	立方/小时	80
	主电机功率(Motor Power)	千瓦(kw)	30X2
	提升电机功率(Hoisting power)	千瓦(kw)	18.5
	水泵电机功率(Pump power)	千瓦(kw)	3
	骨料最大粒径 (碎石/卵石) (Max diameter od aggregates gravel/crushed stone)	毫米(mm)	60/80
	主机外型尺寸(Overall Dimension)	毫米(mm)	3340X2090X1400
	整机质量(Total Weight)	kg	5200
PL2400 四斗配料机 Four Batching	储料斗容积(Storage Bucket Capacity)	m³	15x4
	计量斗容积(Weigher Capacity)	L	2400
	电机功率(Motor Power)	kw	4
	振动电机(Vibvating Motor)	kw	0.3
	外型尺寸(Overall Dimension)	mm	10000X3100X4100
	整机质量(Total Weight)	kg	10000
螺旋输送机 Screw Conveyor	型号(Type)		LSJ65
	输送长度(Converyor Length)	mm	9000
	螺旋体转速(Screw Turning Speed)	r/min	140
	外壳体直径(Diameter)	mm	273
	工作角度(Working Angle)		30-40°
	输送能力(Conveying Ability)	t/h	65
	电机功率(Motor power)	kw	15
	外型尺寸(Overall Dimension)	mm	9000XΦ350
整机质量(Total Weight)	kg	1200	
100t水泥仓 Cement Feeder	外型尺寸(Overall Dimension)	m	20XΦ2.8
水泥计量斗 Cement Weigher	容积(Capacity)	L	800
	外型尺寸(Overall Dimension)	mm	1150x700x1950
水计量斗 Water Weigher	容积(Capacity)	L	300
	外型尺寸(Overall Dimension)	mm	1340x800x1000
外加剂计量斗 Additive Weigher	容积(Capacity)	L	40
	外型尺寸(Overall Dimension)	mm	Φ400x400
空压机 compressor	型号 Type		
	排气量 Discharging Volume	m3/minute	1.6
	额定压力 Rated Pressure	mpa	1
	电机功率(Motor Power)	kw	11

Users may install Cement Silo at own option.

LENOCEAN

HLS100 混凝土搅拌楼 HLS100 CONCRETE BATCHING PLANT

HLS100

- High efficiency, precise weighing system
- Wear-resistance, low maintain cost
- Belt Aggregate Conveyor, large concrete output
- PLC integrated, PC controlled
- Optional Cement Silo and Screw Conveyor



LENOCEAN

BEIJING LENOCEAN TALENT INT. INDUSTRY CORPORATION
www.lenoccean.com

HLS100混凝土搅拌楼性能参数

HLS100 CONCRETE BATCHING PLANT PARAMETERS

BEIJING LENOCEAN TALENT INT. INDUSTRY CORPORATION

www.lenoccean.com

●HLS100

	项目Item	单位Unit	技术参数Technical parameters
JS2000 搅拌机 (Mixer)	出料容积(Discharge Capacity)	升 (L)	2000
	进料容积(Charge Capacity)	升 (L)	3200
	搅拌时间(Mixing Time)	秒s	40-45
	额定生产率(Rated Output)	立方/小时	100
	主电机功率(Motor Power)	千瓦(kw)	37x2
	提升电机功率(Hoisting power)	千瓦(kw)	37
	水泵电机功率(Pump power)	千瓦(kw)	5.5
	骨料最大粒径 (碎石/卵石) (Max diameter od aggregates gravel/crushed stone)	毫米(mm)	60/80
	主机外型尺寸(Overall Dimension)	毫米(mm)	3400X2310X2055
	整机质量(Total Weight)	kg	6700
PL3200 四斗配料机 Four Batching	储料斗容积(Storage Bucket Capacity)	m ³	15x4
	计量斗容积(Weigher Capacity)	L	3200
	电机功率(Motor Power)	kw	4
	振动电机(Vibvating Motor)	kw	0.3
	外型尺寸(Overall Dimension)	mm	10000X3100X4100
	整机质量(Total Weight)	kg	11000
螺旋输送机 Screw Conveyor	型号(Type)		LSJ90
	输送长度(Converyor Length)	mm	11
	螺旋体转速(Screw Turning Speed)	r/min	200
	外壳体直径(Diameter)	mm	273
	工作角度(Working Angle)		30-40°
	输送能力(Conveying Ability)	t/h	90
	电机功率(Motor power)	kw	15
	外型尺寸(Overall Dimension)	mm	11000XΦ350
整机质量(Total Weight)	kg	1500	
100T水泥仓 Cement Feeder	外型尺寸(Overall Dimension)	m	20XΦ2.8
水泥计量斗 Cement Weigher	容积(Capacity)	L	1000
	外型尺寸(Overall Dimension)	mm	1100X800X2160
水计量斗 Cement Weigher	容积(Capacity)	L	500
	外型尺寸(Overall Dimension)	mm	900X700X1100
外加剂计量斗 Cement Weigher	容积(Capacity)	L	40
	外型尺寸(Overall Dimension)	mm	400X400X500
空压机 compressor	型号 Type		
	排气量 Discharging Volume	m ³ /minute	1.6
	额定压力 Rated Pressure	mpa	1
	电机功率(Motor Power)	kw	11

Users may install Cement Silo at own option.